



DURA-LITE 15[®] SCBA CYLINDERS

Features & Benefits



- Significantly improved exterior abrasion resistance
- Uniquely formulated, highly durable exterior coating
- Effective agent against premature cylinder attrition
- Cost effective enhancement to standard cylinders
- Watch the Drag Test video at:
www.SCIfireandsafety.com/products/duralite15.asp
to see the difference between a Standard and DURA-LITE 15[®] cylinder
- Save 30% to 60% off SCBA manufacturer cylinder prices
- Available in 30, 45 & 60 minute durations
- Available in 2216 & 4500 PSI models
- 15 year service life with 5-year hydrostatic testing
- Meets or exceeds all Regulatory Technical Standards – DOT approved
- Custom labeling options available
- Available for all SCBA's

Safety + Reliability + Savings = SCI

DURA-LITE 15® SCBA CYLINDERS

Specifications



DRAG TEST COMPARISON

Watch the Drag Test video to see for yourself why the DURA-LITE 15® is a better option than standard OEM cylinders.

www.SCIfireandsafety.com/products/duralite15.asp

DURA-LITE 15® CYLINDER SPECIFICATIONS

Model	Approx. Duration (min.)	DOT Approval	TC Approval	PSI	Bar	Volume cu. in. (min.)	Volume liter (min.)	OD inches	OD MM (max.)	OAL inches (max.)	OAL MM (max.)	Weight LBS	Weight KG	Port
602D	30	DOT-E 10945	N/A	2216	153	523	8.57	6.84	173.74	19.62	498.84	6.7	3.04	.750-16 UNF-2B
639D	30	DOT-E 10945	N/A	4500	310	285	4.67	5.5	139.7	19.3	490.22	7.12	3.23	.875-14 UNF-2B
603D	45	DOT-E 10945	N/A	4500	310	416	6.82	6.86	174.24	18.2	462.28	9.91	4.5	.875-14 UNF-2B
695D	45	DOT-E 10945	N/A	4500	310	412	6.75	6.32	162.31	20.57	522.48	10.33	4.69	.875-14 UNF-2B
604D	60	DOT-E 10945	N/A	4500	310	550	9.01	7.21	183.14	21.3	541.02	12.3	5.54	.875-14 UNF-2B

NOTE: Specifications are approximate and subject to change without notice.



www.SCIfireandsafety.com

SCIsoba@SCIcomposites.com
325 Enterprise Place • Pomona, CA 91768
909.594.7777