

SNGII-LP

Low Pressure Nitrogen Generators

- › **Pressure**
100 to 175 psig
8 to 12 bar
- › **Capacity**
4.9 to 22.7 scfm
139 to 643 l/min
- › **Power**
15 to 40 hp
11 to 30 kW



The Series II Stationary Nitrogen Generation systems are turnkey solutions designed to generate compressed, high purity nitrogen gas for a diverse range of markets such as plastics processing, industrial, and military applications.

These self-contained, fully integrated systems do not require shop air and eliminate the hazards involved with the handling of high pressure cylinders as well as the burden of merchant-supplied bulk gas. **Why buy Nitrogen when you can make your own?**

SNGII-LP

STANDARD SCOPE OF SUPPLY

- › Feed air compressor, single-stage, air cooled, oil-injected, continuous-duty screw compressor
- › High durability membrane air separators
- › Electric motor (ODP) each with v-belt drive, belt guard and belt tensioning device
- › Automatic condensate drain with collector (includes switch for high condensate level)
- › **UL®** labeled Control Center with PLC controller. Master central system includes interactive touchscreen interface for operation, maintenance and troubleshooting.
- › Single-point power supply connection, fused control voltage transformer
- › On-line percent oxygen monitor
- › Pressure sensors for oil and final product pressure
- › Emergency stop push button
- › Visible alarm annunciation
- › Locally mounted pressure gauges
- › Sound attenuated enclosures for compressors and membrane module
- › Ambient temperature range 40° to 113° F
- › 12 month warranty

AVAILABLE ACCESSORIES

- › Portable percent oxygen monitor
- › CE-complaint electrical assembly
- › TEFC motor
- › Second language for controls / documentation

DIMENSIONS L x W x H inches (mm)

- › ≤ 30 hp, 85 x 59 x 74 (2156 x 1482 x 1867)
- › > 30 hp, 96 x 64 x 84 (2426 x 1626 x 2116)

WEIGHT pounds (kg)

- › ≤ 20 hp, 2200 (821)
- › > 20 hp, 3000 (1120)

SOUND LEVEL (from control panel)

- › ≤ 30 hp, 70 dBA ± 2dBA
- › > 30 hp, 79 dBA ± 2dBA

BUFFER TANK gallon (l)

- › ≤ 20 hp, 60 (227)
- › > 20 hp, 120 (454)

Technical Data

Model	Product flow at 99.5% purity		Product flow at 99.0% purity		Product flow at 98.0% purity		Motor	
	scfm ¹⁾	l/min	scfm ¹⁾	l/min	scfm ¹⁾	l/min	hp	kW
150 psig (10 bar)								
SNGII-15300	5	139	6	176	8	221	15	11
SNGII-20400	8	224	11	306	16	445	20	15
SNGII-30600	18	501	25	697	36	1014	30	22
SNGII-40800	23	643	30	824	38	1065	40	30

1) Capacity (FGD) is referenced to standard conditions. Tolerance +/- 5%.
Dimensions and weight are approximate and are dependent upon model and drive.



North Carolina
210 Labrador Drive
Randleman, NC 27317
Phone 336.674.0749
FAX 336.674.3688
www.safeairsystems.com

North Carolina, South Carolina,
Virginia, Maryland, Delaware
and the District of Columbia
1.800.424.8633