



SlideMaster®

Telescoping Cargo Handler

* Note: Additional \$ for Each 10" In Width Exceeding 40".

* All Units Shown With Optional Tray


**Aluminum
2-Rail
Single Direction
70% Extension**

		Model	Length	Deck Height
	M2 Standard Profile 1000 LB.	15 - 24"	2 7/8"	
		25 - 36"		
		37 - 48"		
		49 - 60"		
		61 - 72"		
		73 - 84"		
		85 - 96"		
	M2-HD Heavy Duty 1500 LB.	15 - 24"	4 1/4"	
		25 - 36"		
		37 - 48"		
		49 - 60"		
		61 - 72"		
		73 - 84"		
		85 - 96"		


**Steel
2-Rail
Single Direction
70% Extension**

		Model	Length (Inches)	Deck Height
	SM2-LP Low Profile 300 LB.	15 - 24"	2 3/8"	
		25 - 36"		
		37 - 48"		
	SM2-MP Mid Profile 600 LB.	15 - 24"	2 7/8"	
		25 - 36"		
		37 - 48"		
		49 - 60"		
	SM2-SP Standard Profile 1000 LB.	15 - 24"	2 7/8"	
		25 - 36"		
		37 - 48"		
		49 - 60"		
		61 - 72"		
		73 - 84"		
	SM2-HD Heavy Duty 2000 LB.	15 - 24"	4"	
		25 - 36"		
37 - 48"				
49 - 60"				
61 - 72"				
73 - 84"				
85 - 96"				
97 - 108"				


**Aluminum
3-Rail
Single Direction
100% Extension**

	Model	Length	Deck Height
	M3 Standard Profile 1000 LB.	15 - 24"	3 1/2"
		25 - 36"	
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
85 - 96"			



**Steel
3-Rail
Single Direction
100% Extension**

	Model	Length (Inches)	Deck Height		
	SM3-LP Low Profile 300 LB.	15 - 24"	2 3/4"		
		25 - 36"			
		37 - 48"			
	SM3-MP Mid Profile 600 LB.	15 - 24"	3 1/4"		
		25 - 36"			
		37 - 48"			
	SM3-SP Standard Profile 1000 LB.	49 - 60"	3 7/8"		
		61 - 72"			
		73 - 84"			
		85 - 96"			
		SM3-HD Heavy Duty 2000 LB.		15 - 24"	4 1/4"
				25 - 36"	
	37 - 48"				
	49 - 60"				
	61 - 72"				
	SM3-HD + Heavy Duty Plus 2500 LB.	73 - 84"	4 1/4"		
		85 - 96"			
		97 - 108"			
		49 - 60"			



**Steel
3-Rail
Single Direction
120% Extension**

	Model	Length (Inches)	Deck Height
	SMEX 700 LB.	25 - 36"	3 7/8"
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
85 - 96"			


**Aluminum
2-Rail
Dual Direction**

	Model	Length	Deck Height
	M2D Standard Profile 1000 LB.	15 - 24"	2 7/8"
		25 - 36"	
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
		85 - 96"	
	M2HD-D Heavy Duty 1500 LB.	15 - 24"	4 1/4"
		25 - 36"	
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
		85 - 96"	

**Steel
2-Rail
Dual Direction**


	Model	Length (Inches)	Deck Height
	SM2-D Standard Profile 1000 LB.	25 - 36"	3 3/8"
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
		85 - 96"	
		97 - 108"	
	SM2-D-HD Heavy Duty 2000 LB.	25 - 36"	3 7/8"
		37 - 48"	
		49 - 60"	
		61 - 72"	
		73 - 84"	
		85 - 96"	
		97 - 108"	

**Aluminum
Tip-Down**


	Model	Length (Inches)	Deck Height
	MT Full Unit 200 LB.	11 - 36"	5 1/2"
		37 - 45"	
		46" +	


	Model	Length (Inches)	Deck Height
	MT-R Rails Only 200 LB.	11 - 36"	5 1/2"
		37 - 45"	
		46" +	


**Steel
Tip-Down**

	Model	Length (Inches)	Deck Height
	SMT Full Unit 250 LB.	9 - 36"	2 5/8"
		37 - 45"	
		46 - 60"	

	Model	Length (Inches)	Deck Height
	SMT-R Rails Only 250 LB.	9 - 36"	2 5/8"
		37 - 45"	
		46 - 60"	

Steel Tool Board Single Direction 70% Extension		Model	Width (Inches)	Deck Height
		SM2-LP T.B. See LP for Length	With Feet – 7 5/16"	2 3/8"
		SM2-MP T.B. See MP for Length	With Feet – 8 9/16" No Feet – 4 9/16"	2 7/8"

Steel Tool Board Single Direction 100% Extension		Model	Width (Inches)	Deck Height
		SM3-LP T.B. See LP for Length	With Feet – 8 1/4" No Feet – 4 1/4"	2 3/4"
		SM3-MP T.B. See MP for Length	With Feet – 11 11/16" No Feet – 7 11/16"	3 1/4"

Steel Tool Board Dual Direction		Model	Width (Inches)	Deck Height
		SM2-D T.B. See Dual Direction For Length	With Feet – 9 1/2" No Feet – 5 1/2"	3 3/8"

Steel Stow Ramp		Model	Length (Inches)
		Stow Ramp	60 - 72"
			73 - 84"
			85 - 96"

Aluminum C to C		Model	Length (Inches)
		C to C 250 LB.	15 - 24"
			25 - 36"
			37 - 48"

OPTIONS / GENERAL INFORMATION

- Notes and Limitations:**
- (1) Additional \$ for each 10" width exceeding 40" except for (2) below.
 - (2) For aluminum C to C and Tip Down: Additional \$ for each 10" exceeding 35".
 - (3) Spring Lock (HSL) available on Mid-Profile, Standard-Profile and HD Aluminum Only.
 - (4) Minimum length for a Spring Lock: 3-Rail is 17 1/2"; 2-Rail is 16"
 - (5) Minimum width for a Spring Lock *with feet* is 20" and *no feet* is 16"
 - (6) Minimum width for Heavy Duty Spring Lock *with feet* is 28" and *no feet* is 24".
 - (7) Guide Bearing for Steel 2-Rail and 3-Rail MP, SP and HD Units Only.

Spring Lock (HSL) (Steel or Aluminum) Note (3) (4) (5) (6)	2-Rail Unit	3-Rail Unit

Powder Coating (Steel Only)	Length (Longest Dimension)	2-Rail Unit	3-Rail Unit
	0 - 48"		
	49 - 60"		
	61 - 72"		
	73 - 84"		
	85 - 96"		

For 109" or more, call for price.
Please add 14 days so the fabricating process for the powder coating option.

Tray (Steel Only, Call for widths greater than 42"	Length (Longest Dimension)
	9 - 24"
	25 - 36"
	37 - 48"
	49 - 60"
	61 - 72"
	73 - 84"
	85 - 96"

Electric Drive Alum. Single or Dual Direction 70% Ext. and Steel Single Direction 90% Ext.	Motor drive with manual switch
	Infrared remote - single direction
	Infrared remote - dual direction

Guide Bearings
For units with widths two times the length: Additional \$